



DW60

Four-wheel dumpers: payload > 5 t



The power house – wheel dumper DW60.

The wheel dumper has everything a key player needs: hydrostatic four-wheel drive, 2 types of skip, 6,000 kg payload and a powerful engine. And the modern safety cab turns it into an all-season dumper - all fitted ex-works.

- More power: DW60 Power model with an engine output of 86 kW
- 2 types of skip: Front-tipping skip (standard), swivel tipping skip (optional); up to 3,200 I skip capacity (heaped) as standard
- Supreme off-road capability thanks to a center-pivot angle of up to 29 degrees
- A top speed of 25km/h gets transport jobs done fast
- Optional cab available ex-works

wackerneuson.com - 31.05.2015 Page: 1/5



Technical specifications

DW60

Operating data

Payload	6,000 kg
Shipping weight Front tip skip ROPS	4,483 kg
Shipping weight Front tip skip cabin	4,683 kg
Shipping weight Swivel skip ROPS	4,866 kg
Shipping weight Swivel skip cabin	5,066 kg
Skip capacity Swivel skip, levelled	2,350
Skip capacity Swivel skip, heaped	3,200
Skip capacity Swivel skip, water level	1,660 l
Skip capacity Front skip, levelled	2,650 l
Skip capacity Front skip, heaped	3,500
Skip capacity Front skip, water level	1,900 l

Engine / Motor

Engine / Motor manufacturer	Perkins
Engine / Motor type	854F
Engine / Motor	watercooled 4cylinder turbodiesel
Engine performance acc. to ISO 3046/1	55 kW
Displacement	3,400 cm ³
Engine RPM	2,500 rpm
Emissions	Stage 3b / Tier 4 final
Traction drive	4WD, hydrostatic
Travel speed	25 km/h
Articulation angle	29 °
Pendulum angle	11 °
Tires	405/70-20
Steering pump	Axial piston pump
Flow rate	152 l/min
Operating pressure	150 bar
Duty pump	Gear pump
Operating pressure	235 bar
Tank capacity	82.5

wackerneuson.com – 31.05.2015 Page: 2 / 5





Hydraulic oil tank 55 I

DW60 Power

Engine / Motor

Engine / Motor manufacturer	Perkins
Engine / Motor type	854E
Engine / Motor	watercooled 4cylinder turbodiesel
Engine performance	86 kW
Displacement	3,400 cm ³
Engine RPM	2,500 rpm
Emissions	Stage 3b / Tier 4 interim

DW60 LRC

Engine / Motor


Engine / Motor manufacturer	Perkins
Engine / Motor type	1104D
Engine / Motor	watercooled 4cylinder turbodiesel
Engine performance	62.5 kW
Displacement	4,400 cm ³
Engine RPM	2,400 rpm
Emissions	Stage 3a / Tier 3
Tires	400/55R22.5
Tires	400/55R22.5

wackerneuson.com – 31.05.2015 Page: 3 / 5





Dimensions



C1	Overall width	2,250 mm
C2	Skip width swivel skip	2,091 mm
D	Width	1,810 mm
F	Ground clearance	369 mm
H2	Skip height	2,075 mm
H4	Skip height tilted	3,524 mm
K1	Tip-out angle	48 °
A1	Height total (ROPS)	3,348 mm
АЗ	Height tilted ROPS	2,299 mm
B2	Length	4,934 mm
Е	Wheelbase	2,485 mm
G2	Rear overhang	1,192 mm
G1	Distance Mulde gekippt und Rad	842 mm

wackerneuson.com – 31.05.2015 Page: 4 / 5



Please note

that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions. Subject to alterations and errors excepted. Applicable also to illustrations.

Copyright © 2015 Wacker Neuson SE.

wackerneuson.com – 31.05.2015 Page: 5 / 5